



Multiscale testing of composite steel interfaces for blade root bushing connections

Rezaei, Mohsen; Berggreen, Christian

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Rezaei, M., & Berggreen, C. (2017). *Multiscale testing of composite steel interfaces for blade root bushing connections*. Abstract from 2nd International Symposium on Multiscale Experimental Mechanics was Multiscale Fatigue., Kongens Lyngby, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



ISMEM 2017

- 2nd International Symposium on Multiscale
Experimental Mechanics: Multiscale Fatigue



Multi-scale testing of composite steel interfaces for blade root bushing connections

Mohsen Rezaei, Mads Borgnæs, Christian Berggreen

Department of Mechanical Engineering, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark

e-mail: : morez@mek.dtu.dk, cbe@mek.dtu.dk



Mohsen Rezaei, Research scientist at DTU Mechanical engineering, research interest includes fracture mechanics, structural analysis, testing of composites and degradation of adhesive joints at aggressive conditions.



Christian Berggreen, Head of Lightweight Structures Group, primary research interests includes experimental mechanics, hybrid testing, composite materials and structures.

Abstract

Given the societal, environmental and design requirements, there is an ever increasing interest in designing wind turbine blades. To this end, given the increasing length of wind turbine blades, lightweight and high performance designs of the blade root end are essential to connect wind turbine blades to the rotors. However, an increase in the ratio of length to diameter of wind turbine blade exerts higher loads on the connections located at the maximum moment location. The carrot joint root bushing connection type is becoming popular in the wind industry, since if placed relatively close together, they do not have any adverse effect on the root blade strength. The static and dynamic strength of the root bushing connections are commonly determined experimentally by a sub-component test, which typically is carried out by a static and cyclic fatigue pull-out test of the bushing according to the Germanischer Lloyd standard [1].

In this work, the root bushing connections in a wind turbine blade under multi-axial loading are analyzed using fracture mechanical analysis methods. The required material properties, such as the critical energy release rates for mode-I, mode-II and mixed-mode are characterized experimentally through Double Cantilever Beam specimens with Uneven Bending Moments (DCB-UBM). In the intermediate step, the obtained results from DCB-UBM tests are used to analyze and validate the cohesive interface between the metallic and composite substrates in Double Strap Joint (DSJ).

Next, the validated results from DCB-UBM and DSJ tests are used to analyze the cohesive interface between the metallic bushings and composite root body using cohesive elements in FEA. The model outputs are further validated by testing an actual wind turbine bushing under multi-axial loading (see figure 1). This developed analysis model can be used to forecast failure of the root end bushings in terms of their circumferential location in wind turbine blade root.



Figure 1. Test set-up for testing of wind turbine root bushing under multiaxial loading

REFERENCES

- [1] Germanischer Lloyd, "Fibre Reinforced Plastic (FRP) and Bonded Joints," in *Guideline for the Certification of Wind Turbines*, 2010, pp. 5-26